

### Features

- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip(s)
- UL® 1069 Listed

### Description

The TekTone® SF301G Call Cord is for use with Tek-CARE® nurse call systems and wireless emergency call systems where ¼" phono jacks are used.

The SF301G Call Cord is specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient applies slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF301G and is attached to the call cord.

### Listings

UL® 1069 Listed; UL® File Number E71599.



### Specifications

|             |   |
|-------------|---|
| Switch:     | Momentary contact, air activated  |
| Plug:       | Stainless steel   |
| Cord:       | Vinyl tubing  |
| Electrical: | Rated current 1/3 AMP, 24 VAC-VDC   |
| Dimensions: | Cord: 6' long (1.83 m)<br>Plug: 1.25" long (32 mm)<br>Bulb: 1.5" diameter (38 mm) |



SF301G Call Cord

### Required Components

Tek-CARE®500 Wireless Nurse Call System with SF521UL or SF523UL Room Stations  
or  
Tek-CARE®120 or 160 Nurse Call System with SF121 or SF122 Room Stations  
or  
Tek-CARE®300II Nurse Call System with SF380A Patient Stations  
or  
Tek-CARE® NC200N or NC150N Nurse Call Systems with IR151B or IR152B Patient Stations  
or  
Tek-CARE® NC110N Nurse Call System with SF100C or SF102 Patient Stations