

Features

- Call type is indicated by one of four colored LEDs
- A call tone sounds for the highest priority call
- UL/cUL®1069 and UL®2560 Listed
- RoHS Compliant

Description

The SF125 Duty Station annunciates calls both audibly and visually via 4 colored LEDs and a tone speaker. The various call priorities will be indicated by the LEDs and the highest level call will be annunciatted by time. Watched zones are programmable via the LS450 Config Tool.

The SF125 Duty Station connects via the LI122UN Room Controller with Dome Light or the PM120 Room Controller, using 2 of the 6 connection points. Each NC120 or NC160 Central Equipment Module supports up to 24 duty stations (6 duty stations per run) depending on power restrictions. Refer to the Tek-CARE® [Master Station Load Value Calculator](#) on TekTone's website for more information on power restrictions.

The station's plastic bezel snaps onto the included mounting plate, leaving no visible screw holes.

Listings



UL® 1069 Listed and cUL® Listed to
CSA C22.2 No. 205;
UL® File Number E71599.



RoHS Compliant.



SF125 Duty Stations

Specifications

- Dimensions: 4.58"H × 6.74"W × 1.03"D
(116 mm × 171 mm × 26 mm)
- Environment: 5%–95% non-condensing humidity;
0°C–60°C
- Construction: PC board with quality electronic components mounted on a flame-retardant (UL® 94V-0) plastic faceplate
- Mounting: Attach included back plate to a standard single- or dual-gang ring, or single- or dual-gang ring and box
- Connections: 2-wire flying lead, a plus 2 screw terminals for the toner module. Uses 2 of the station module's 6 points

Required Components

NC120 or NC160 Central Equipment Module
PM120, LI122UN Room Controller

Optional Components

NC415G3 or NC404TS Master Station