

Features

- Tappable at 8, 16, or 24 VAC
- UL® Listed Class 2 transformer
- Pre-stripped pigtailed for primary connections
- Screw terminals for secondary connections
- Surface mounted or via a standard 1/2" knockout on an electrical box

Description

TekTone's SS106 Class 2 Transformer offers a compact, easy-to-install low voltage AC power source for use with various TekTone® Tek-CARE® systems. The SS106 Transformer is a UL® Listed Class 2 transformer and will safely take itself offline when overheated.

The transformer is constructed for easy surface installation or in a standard 1/2" knockout, and may be used in plastic or metal boxes. Primary wire connections are made using the pre-stripped pigtailed and ground wire; secondary connections are made using screw terminals.

Optional Components

Various Tek-CARE Systems, including:

CM800, DS100, NC110, NC150, and NC200 Nurse Call Systems



SS106 Transformer

Specifications

120 VAC primary
8 VAC 20 VA, 16/24 VAC 30 VA secondary

Dimensions

Faceplate:	1.25"H × 5.875"W (31.8 mm × 149 mm)
Case width:	0.9375" (24 mm)
Case depth:	1.4375" (35 mm)
Latch opening:	1.375" (35 mm)

Note: The SS106 is found in the power and control assembly; IH151NK and the battery back-up assembly; PK124K.