

Tek-CARE Nurse Call and Wireless Nurse Call Systems • Rev. 26 - 1/2023

Features

- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included
- UL® 1069 Listed; SF301A is also UL® 2560 Listed

Description

The TekTone SF301A (single) or SF302 (double) Call Cords are for use with the Tek-CARE® nurse call systems and wireless emergency call systems where 1/4" phono jacks are used. Ten-foot cords are also available as SF301A/10 and SF302/10. The SF301A and SF302 are oxygen safe call cords certified safe for use by all patients receiving oxygen therapy. These waterproof and impact-resistant call cords have comlpetely sealed push buttons.

Required Components

Tek-CARE® 500 Wireless Nurse Call System with SF521UL

Tek-CARE® 120 or 160 Nurse Call System with SF121 or SF122 Room Stations

Tek-CARE® 300II Nurse Call System with SF380A Patient Stations

Tek-CARE $^{\circledR}$ NC200N or NC150N Nurse Call Systems with IR151B or IR152B

Tek-CARE® NC110N Nurse Call System with SF100C or SF102 Patient Stations

Listings



SF301A is UL[®] 1069 and UL[®] 2560 Listed; SF302 is UL[®] 1069 Listed; UL[®] File Number E71599.





SF301A, SF302 Call Cord

Specifications

Dimensions: 7' (2.13 m) long polyvinyl-covered cord

Construction: SPST-1A switch, Integral brass, fine sil-

ver contacts 1 AMP, 115 watt maximum,

AC

Connections: 1/4" (6.35 mm) plug-in phono jack